



SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

SDS # : 083359

KILFROST AIRTOOL LUBE

Date of the previous version: not applicable

Revision Date: 2015-05-11

Version 1

1. IDENTIFICATION

Product identifier

Product name KILFROST AIRTOOL LUBE

Other means of identification

Product Code(s) 083359

Number 7Z3

Substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Identified uses Antifreeze. Lubricant.

Uses advised against Do not use for any purpose other than the one for which it is intended

Details of the supplier of the safety data sheet

Supplier Address TOTAL Specialties USA Inc
1201 Louisiana Street, Suite 1800
Houston, TX 77002
Phone: +1 800 323 3198

Contact Point Technical/ HSEQ

E-mail Address USRMLIN-info@total.com

Emergency telephone number

Company Phone Number

+1 (908) 862-9300

Emergency telephone

CHEMTREC: +1 800 424 9300 (24h)

2. HAZARDS IDENTIFICATION

Classification

Acute Toxicity - Oral - Category 4

Specific target organ systemic toxicity (repeated exposure) - Category 2

Label elements



SDS # : 083359

KILFROST AIRTOOL LUBE

Date of the previous version: not applicable

Revision Date: 2015-05-11

Version 1



WARNING

Harmful if swallowed
May cause damage to organs through prolonged or repeated exposure

Precautionary Statements - Prevention

Do not breathe dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product

Precautionary Statements - Response

Get medical advice/attention if you feel unwell

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
Rinse mouth

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Unknown Acute Toxicity

No information available

Hazards not otherwise classified (HNOC)

- Causes mild skin irritation

Other information

- Contaminated surfaces will be extremely slippery
- Should not be released into the environment

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Monoethyleneglycol	107-21-1	55-60
Benzene, mono-C10-13-alkyl derivatives, fractionation bottoms, heavy ends, sulfonated, sodium salts	148520-82-5	5-10
Benzenesulfonic acid, C10-14-alkyl derivatives, sodium salts	69669-44-9	1-5



SDS # : 083359

KILFROST AIRTOOL LUBE

Date of the previous version: not applicable

Revision Date: 2015-05-11

Version 1

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice	Show this material safety data sheet to the doctor in attendance. If symptoms persist, call a physician. Do not breathe dust/fume/gas/mist/vapors/spray. IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing.
Skin contact	Consult a physician if necessary. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Remove contaminated clothing and shoes.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. Consult a physician. Inhalation of high concentrations of vapor or aerosols may cause irritation of the upper respiratory tract.
Ingestion	If symptoms persist, call a physician. Rinse mouth. Do NOT induce vomiting. If swallowed, do not induce vomiting - seek medical advice. Never give anything by mouth to an unconscious person.
Protection of First-aiders	Use personal protective equipment.

Most important symptoms/effects, acute and delayed

Skin contact	Causes mild skin irritation.
Eye contact	Not classified. Avoid contact with eyes. May cause eye irritation with susceptible persons.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Harmful if swallowed. May cause damage to organs through prolonged or repeated exposure. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Symptoms	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Itching. Difficulty breathing. Coughing and/ or wheezing.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treat symptomatically. May cause sensitization of susceptible persons.
---------------------------	--

5. FIRE-FIGHTING MEASURES

<u>Suitable Extinguishing Media</u>	Foam. Carbon dioxide (CO ₂). ABC powder.
<u>Unsuitable Extinguishing Media</u>	Do not use a solid water stream as it may scatter and spread fire.
<u>Special Hazard</u>	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.



SDS # : 083359

KILFROST AIRTOOL LUBE

Date of the previous version: not applicable

Revision Date: 2015-05-11

Version 1

Explosion Data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective Equipment and Precautions for Firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General Information Avoid contact with skin, eyes and clothing. Use personal protective equipment. Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Evacuate personnel to safe areas. Ensure adequate ventilation.

Other information See Section 12 for additional information.

Environmental precautions

General Information Prevent entry into waterways, sewers, basements or confined areas. Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained. Try to prevent the material from entering drains or water courses. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for cleaning up Dam up. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use mechanical means such as pumps and absorbent materials.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Wear personal protective equipment. Prevent the formation of vapors, mists and aerosols. When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist.

Hygiene measures

Regular cleaning of equipment, work area and clothing is recommended. Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Use personal protective equipment as required. Wash hands before breaks and at the end of workday. Avoid breathing vapors, mist or gas. Avoid prolonged and repeated contact with the skin, especially with used or waste product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets. When using, do not eat, drink or smoke.



SDS # : 083359

KILFROST AIRTOOL LUBE

Date of the previous version: not applicable

Revision Date: 2015-05-11

Version 1

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Keep away from direct sunlight. Keep container tightly closed in a dry and well-ventilated place. Keep in a bunded area. Keep out of reach of children.

Materials to Avoid Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits Mineral oil mist:
USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined).

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Monoethyleneglycol 107-21-1	Ceiling 100 mg/m ³	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m ³	

Exposure controls

Engineering Measures Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Individual protection measures, such as personal protective equipment

General Information If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.

Eye/Face Protection If splashes are likely to occur, wear: Safety glasses with side-shields.

Skin and body protection Long sleeved clothing. Wear suitable protective clothing. Protective shoes or boots.

Hand Protection Protective gloves. Nitrile rubber. Neoprene gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.



SDS # : 083359

KILFROST AIRTOOL LUBE

Date of the previous version: not applicable

Revision Date: 2015-05-11

Version 1

Hygiene measures

Regular cleaning of equipment, work area and clothing is recommended. Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Use personal protective equipment as required. Wash hands before breaks and at the end of workday. Avoid breathing vapors, mist or gas. Avoid prolonged and repeated contact with the skin, especially with used or waste product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets. When using, do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Color	amber
Physical State @20°C	liquid
Odor	Slight
Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH		No information available	
pH (as aqueous solution)	8.2	solution (50 %)	
Melting point/range		No information available	
Boiling point/boiling range		Not applicable	
Flash point		Not applicable	
Evaporation rate		No information available	
Flammability Limits in Air		No information available	
upper	-	No information available	
Lower	-	No information available	
Vapor Pressure		No information available	
Vapor density		No information available	
Relative density	1.07	@ 15 °C	
Density	1071 kg/m ³	@ 15 °C	
Water solubility		Not applicable	
Solubility in other solvents		No information available	
logPow		No information available	
Autoignition temperature		No information available	
Decomposition temperature		No information available	
Viscosity, kinematic	24.7 mm ² /s	@ 40 °C	
Explosive properties	Not explosive		
Oxidizing Properties	Not applicable		
Possibility of hazardous reactions	Not applicable		
<u>Other information</u>			
Specific Gravity	1.07	@ 15 °C	
Freezing Point		No information available	
Pour point	-45.5 °C		ASTM D 97

10. STABILITY AND REACTIVITY



SDS # : 083359

KILFROST AIRTOOL LUBE

Date of the previous version: not applicable

Revision Date: 2015-05-11

Version 1

Reactivity	No information available.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to Avoid	Heat, flames and sparks. Take precautionary measures against static discharges. Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Strong oxidizing agents.
Incompatible Materials	Strong oxidizing agents.
Hazardous Decomposition Products	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Information on likely routes of exposure

Product Information

Skin contact	Causes mild skin irritation.
Eye contact	Not classified. Avoid contact with eyes. May cause eye irritation with susceptible persons.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Harmful if swallowed. May cause damage to organs through prolonged or repeated exposure. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Numerical measures of toxicity - Product Information

ATEmix (oral)	719 mg/kg
ATEmix (dermal)	5338 mg/kg
Inhalation	
ATEmix (inhalation-dust/mist)	7.5 mg/l
ATEmix (inhalation-vapor)	234.4 mg/l

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Monoethyleneglycol 107-21-1	LD50 7712 mg/kg Oral (Rat)	LD50 > 3500 mg/kg Dermal (Mouse)	LC50(6h) >2.5 mg/l Inhalation (Rat)
Benzene, mono-C10-13-alkyl derivatives, fractionation bottoms, heavy ends, sulfonated, sodium salts 148520-82-5	404 mg/kg (Rat)		



SDS # : 083359

KILFROST AIRTOOL LUBE

Date of the previous version: not applicable

Revision Date: 2015-05-11

Version 1

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Itching. Difficulty breathing. Coughing and/ or wheezing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Not classified as a sensitizer. Contains sensitizer(s).
Carcinogenicity This product is not classified carcinogenic.

Mutagenicity This product is not classified as mutagenic.
Reproductive toxicity This product does not present any known or suspected reproductive hazards.
STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.
Aspiration Hazard Not classified.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Acute aquatic toxicity - Product Information

No experimental data available

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms
Monoethyleneglycol 107-21-1	EC50(48h) >10000 mg/l	LC50 (95h) 72860 mg/l (Phimephales promelas) LC50(96h) 18500 mg/l (Rainbow trout) EC50(96h) 6500-13000 mg/l (Selenastrum capricornulum)	EC50(48h) >100 mg/l Daphnia magna (OECD 202)	

Chronic aquatic toxicity - Product Information

No experimental data available

Chronic aquatic toxicity - Component Information

No information available

Effects on terrestrial organisms No experimental data available .

Persistence and degradability

General Information No information available.



SDS # : 083359

KILFROST AIRTOOL LUBE

Date of the previous version: not applicable

Revision Date: 2015-05-11

Version 1

Bioaccumulative potential

Product Information No information available.

logPow No information available

Component Information

Chemical Name	log Pow
Monoethyleneglycol 107-21-1	-1.2

Mobility

Soil No information available

Other adverse effects

General Information No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods Dispose of in accordance with local regulations.

Contaminated packaging Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

MEX Not regulated

ICAO/IATA Not regulated

IMDG/IMO Not regulated

ADR/RID Not regulated

ADN Not regulated

15. REGULATORY INFORMATION



SDS # : 083359

KILFROST AIRTOOL LUBE

Date of the previous version: not applicable

Revision Date: 2015-05-11

Version 1

International Inventories

All the substances contained in this product are listed or exempted from listing in the following inventories:

U.S.A. (TSCA)
Australia (AICS)
Canada (DSL/NDSL)

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	no
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Chemical Name	CAS-No	Weight %	HAPS data	VOC Chemicals	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Monoethyleneglycol	107-21-1	55-60		Group I		

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs
Monoethyleneglycol	5000 lb	

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Monoethyleneglycol 107-21-1	X	X	X	X	X
Distillates (petroleum), hydrotreated light naphthenic 64742-53-6	X				



SDS # : 083359

KILFROST AIRTOOL LUBE

Date of the previous version: not applicable

Revision Date: 2015-05-11

Version 1

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazard 2	Flammability 0	Instability 0	Physical and chemical hazards -
<u>HMIS</u>	Health Hazard 2	Flammability 0	Physical Hazard 0	Personal protection X

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

Revision Date: 2015-05-11
 Revision Note: No information available
 Abbreviations, acronyms

Legend

Section 8
 ACGIH - American Conference of Governmental Industrial Hygienists
 OSHA - Occupational Safety and Health Administration
 NIOSH - National Institute for Occupational Safety and Health
 TLV - Threshold Limit Values
 PEL - Permissible Exposure Limits
 IDHL - Immediately Dangerous to Life or Health concentrations
 TWA - Time Weight Average
 STEL - Short Term Exposure Limits
 S* - Skin notation
 TSCA - Toxic Substance Control Act

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of the safety data sheet