

### SECTION 1: Identification

#### 1.1. Product identifier

Product form : Mixture  
 Product name : Natco Inner Liner Repair Seal  
 Product code : RS16 (16 oz. can), RS32 (32 oz. can)  
 Formula : Trichloroethylene and Rubber Blend  
 Chemical Family : Rubber Compound

#### 1.2. Recommended use and restrictions on use

Recommended use : Tire Inner Liner Sealer

#### 1.3. Supplier

Natco Manufacturing Ltd.  
 1456 Church Avenue  
 Winnipeg, Manitoba  
 R2X 1G4  
 Ph: (204) 633-5432  
 Fax: (204) 694-3320

#### 1.4. Emergency telephone number

Emergency number : Canutec: (613) 996-6666 (Canada), Chemtrec: (800) 424-9300 (USA)

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

**Classification (GHS CA)** : This material is considered hazardous by Health Canada Hazardous Product regulations (WHMIS 2015), and by the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

Skin Corrosion / Irritant : Category 2  
 Serious Eye Damage / Eye Irritant : Category 2  
 Skin Sensitization : Category 1  
 Germ Cell Mutagenicity : Category 2  
 Carcinogenicity : Category 1A  
 STOT, Single Exposure  
 --Target Organs - Central Nervous System (CNS) : Category 3  
 STOT, Repeated Exposure  
 -- Target Organs - Kidney, Liver, Heart, Spleen,  
 and Blood : Category 2

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-CA labelling

**Signal Word** : **Danger!**

##### Pictograms



GHS06 Toxic



GHS07 Harmful



GHS08 Health Hazard

##### Hazard Statements

H315 : Causes skin irritation  
 H319 : Causes serious eye irritation  
 H334 : May cause an allergic skin reaction  
 H336 : May cause drowsiness or dizziness  
 H341 : Suspected of causing genetic defects  
 H350 : May cause cancer  
 H373 : May cause damage to organs through prolonged or repeated exposure

# Natco Inner Liner Repair Seal

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 06/11/2019

Revision date: 01/06/2020

Version: 2.0

### Precautionary Statements -- For Prevention

- P201 : Obtain special instructions before use
- P202 : Do not handle until all safety precautions have been read and understood
- P260 : Do not breathe dust / fumes / gas / mist / vapors/ spray
- P264 : wash face, hands and any exposed skin thoroughly after handling
- P271 : Use only outdoors or in a well-ventilated area
- P272 : Contaminated work clothing should not be allowed out of the workplace
- P280 : Wear protective gloves, protective clothing, eye protection and / or face protection

### Precautionary Statements -- For Response

- P308 : IF exposed or concerned -- Get medical attention / advice
- P304 + 340 : IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- P302 : IF ON SKIN: Wash with plenty of soap and water
- P362 + 364 : Take off contaminated clothing and wash before re-use
- P333 + 313 : If skin irritation or rash occurs, get medical advice / attention
- P305 + 351 + 338 : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing
- P337 + 313 : If eye irritation persists, get medical advice / attention

### Precautionary Statements -- For Storage

- P403 : Store in a well-ventilated place. Keep container tightly closed
- P405 : Stock locked up

### Precautionary Statements -- For Disposal

- P501 : Dispose of contents / container to an approved waste disposal plant

### 2.3. Other hazards

Harmful to aquatic life with long lasting effects.

WARNING! This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%
Trichloroethylene	CAS: 79-01-6	25 - 40%
Carbon Black		< 5% *
Aromatic / Naphthenic Oil		< 5% *

\* Exact Formula — Proprietary Generated by Natco Manufacturing Ltd.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require no reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Do not use mouth-to-mouth method, give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
- First-aid measures after skin contact : Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
- First-aid measures after eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.
- First-aid measures after ingestion : Do not induce vomiting. Call a physician or Poison Control Center immediately.

# Natco Inner Liner Repair Seal

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 06/11/2019

Revision date: 01/06/2020

Version: 2.0

### 4.2. Most important symptoms and effects (acute and delayed)

General Information	: No symptoms/effects reasonably foreseeable.
Symptoms/effects after inhalation	: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Symptoms of allergic reaction may include rash, itching, swelling. May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea

### 4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : In case of accident or if you feel unwell, seek medical advice immediately (show the label and this Safety Data Sheet to medical professional)

Notes to Physician : Treat symptomatically

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media : Use fire extinguishing media appropriate for surrounding materials.

### 5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use water jet as an extinguisher, as this will spread the fire.

### 5.3. Specific hazards arising from the hazardous product

Contact with metals may evolve flammable hydrogen gas. Fire may produce irritating, corrosive and / or toxic gases.

### 5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Fire-fighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, when battling fires in enclosed spaces. Standard breathing apparatus (SCBA with a full face-piece operated in positive pressure mode) should also be used or available for use if needed

Special Firefighting Procedures : Move containers from the fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. Cool containers exposed to flames with water until well after the fire is out.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding area. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. Also see the information in "For non-emergency personnel".

### 6.2. Methods and materials for containment and cleaning up

For containment and cleaning up : Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination. Dike far ahead of larger spill for later recovery and disposal. Ventilate contaminated area. Contaminated soil must be dug up and treated to protect groundwater. Dispose of via a licensed waste disposal contractor. Package all material in plastic, cardboard or metal containers for disposal in accordance with federal, state, provincial and local regulations.

Notification procedures : Dike for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. Inform authorities if large amounts are involved.

Environmental precautions : Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

### 6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

# Natco Inner Liner Repair Seal

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 06/11/2019

Revision date: 01/06/2020

Version: 2.0

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Protective measures

- : Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Do not taste or swallow. Do not eat, drink or smoke when using this product. Avoid contact with eyes and skin. Wear protective gloves, clothing and eye and face protection. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material. Keep tightly closed when not in use. Store in a cool dry area. Use only in area well ventilated. Avoid breathing vapors. Harmful or Fatal if Swallowed.
- : Open container slowly to relieve any pressure. The use of appropriate respiratory protection is advised when concentrations exceed any established exposure limited (see Section 8). Wash thoroughly after handling. Do not wear contaminated clothing or shoes. Keep contaminated clothing away from sources of ignition such as sparks or open flames. Use good personal hygiene practice.
- : "Empty" containers retain residue and may be dangerous. Do not re-use containers. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury or death. "Empty" drums should be completely drained, properly bunged and promptly shipped to the supplier or a drum re-conditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

Advice on general occupational hygiene

- : Before working on/in tanks which contain or have contained this material, refer to OSHA Regulations, and other governmental and industrial references pertaining to cleaning, repairing, welding or other contemplated operations.
- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking and after contact with material. Remove contaminated clothing and protective equipment before entering eating areas. Also see Section 8 for additional information on hygiene measures.

#### 7.2. Conditions for safe storage, including any incompatibilities

Conditions for safe storage, including any incompatible

- : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well ventilated area, away from all sources of ignition, incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Avoid basement storage which may lead to trapping of heavy vapor. Smoking in the presence of the product vapor is hazardous due to its decomposition into toxic gases. Post area "No Smoking or Open Flame". Protect containers against physical damage. Outdoor or detached storage is preferred. Store in a cool, well ventilated area away from heat, oxidizers and all sources of ignition.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Trichloroethylene	TWA: 10 ppm STEL: 25 ppm	(Vacated) TWA: 50 ppm (Vacated) TWA: 270 mg/m <sup>3</sup> Ceiling: 200 ppm (Vacated) STEL: 200 ppm (Vacated) STEL: 1080 mg/m <sup>3</sup> TWA: 100 ppm	IDLH: 1000 ppm	TWA: 100 ppm TWA: 535 mg/m <sup>3</sup> STEL: 200 ppm STEL: 1080 mg/m <sup>3</sup>
Carbon Black	None	None	None	None
Aromatic / Naphthenic Oil	None	None	None	None

Legend

**ACGIH - American Conference of Governmental Industrial Hygienists**

**OSHA - Occupational Safety and Health Administration**

**NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health**

# Natco Inner Liner Repair Seal

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 06/11/2019

Revision date: 01/06/2020

Version: 2.0

### 8.2. Appropriate engineering controls

- Appropriate engineering controls : Use only under a chemical fume hood. Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location.
- Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

- General Information** : Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
- Hand protection** : Chemical resistant, impervious gloves that are resistant to the product and/or substance being prepared should be worn at all times when handling chemical products. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection** : The use of a face shield and chemical goggles to safeguard against potential eye contact, irritation or injury is recommended.
- Skin and body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.  
: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved
- Respiratory protection** : A NIOSH or MSHA approved air purifying respirator with an organic vapor cartridge may be used under conditions where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited (see manufacturer's respirator selection guide). Use a positive pressure air supplied respirator if there is potential for uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.  
: A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.
- Hygienic measures** : Wash hands, forearms and face thoroughly after handling chemical products and before eating, drinking, smoking and using the lavatory and at the end of the working period.  
: Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before re-using. Ensure that eyewash stations and safety showers are close to the workstation location.
- Other information** : The usual precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages, and feed. Remove all soiled and contaminated clothing.  
: Handle in accordance with good industrial hygiene and safety procedures.  
: Do not eat, drink or smoke when using this product.  
: Eye wash and quick-drench shower facilities should be available in the work area. Thoroughly clean shoes and wash contaminated clothing before re-use. It is recommended that impervious clothing be worn.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Color : Black
- Odor : Characteristic
- Odor threshold : No information available
- pH : No information available
- Melting point / range : -85° C / -121° F
- Boiling point / range : 87° C / 188.6° F
- Flash point : No information available
- Evaporation rate : 0.69 (Carbon Tetrachloride = 1.0)
- Flammability (solid, gas) : Not applicable
- Flammability or explosive limits : Upper: 10.5 vol%  
Lower: 8 vol%
- Vapor pressure : 77.3 mbar @ 20° C
- Vapor density : 4.5 (AIR = 1.0)
- Specific Gravity : 1.460
- Solubility : Slightly soluble in water
- Partition coefficient: n-octanol / water : No data available
- Auto-ignition Temperature : 410° C / 770° F
- Decomposition temperature : > 120° C
- Viscosity : 0.55 mPa.s (25° C)
- Molecular formula : C2 H C13
- Molecular weight : 131.39

# Natco Inner Liner Repair Seal

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 06/11/2019

Revision date: 01/06/2020

Version: 2.0

### SECTION 10: Stability and reactivity

#### 10.1. Stability and Reactivity

- Stability : Stable under normal conditions of use and storage. Will slowly decompose to hydrochloric acid when exposed to light and moisture.
- Reactivity : No dangerous reaction known under conditions of normal use.
- Polymerization : Will not occur
- Conditions to avoid : Avoid all possible sources of ignition (heat, flame, or spark). Light, moisture, and incompatibles.
- Materials to avoid : Avoid contact with strong oxidizing agents. Alkalines and caustics. Chemically active metals.
- Hazardous decomposition products : May produce carbon monoxide, carbon dioxide, hydrogen chloride and phosgene when heated to decomposition. By heating and fire, toxic vapors / gases may be formed.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

- Potential Health Effects
- Eye contact : Eye irritant. Contact may cause stinging, watering, redness, swelling and eye damage.
- Skin contact : Skin irritant. Contact may cause redness, itching, burning and skin damage. Prolonged or repeated contact can worsen by causing drying and cracking of the skin, leading to dermatitis (inflammation). Repeated contact with a component may cause an allergic reaction. Low degree of toxicity by skin absorption.
- Inhalation : Low to moderate degree of toxicity by inhalation.
- Ingestion : Low degree of toxicity by ingestion. **ASPIRATION HAZARD:** — This material can enter lungs during swallowing or vomiting and cause inflammation and damage. A component may cause alcohol intolerance (Antabuse Effect) if swallowed.
- Signs & Symptoms : Effects of over-exposure may include nausea, vomiting, irritation of the respiratory and digestive tracts, transplant excitation followed by signs of nervous system depression (eg., headache, drowsiness, dizziness, loss of co-ordination, disorientation and fatigue).
- Cancer : A component is a probable cancer hazard.
- Oral product : LD 50 (Rat): 4,920 mg/kg
- Dermal product : No data available
- Inhalation product : LC 50 (Rat, 4 hr): 12,000 ppm
- Repeated dose toxicity product : No data available
- Skin corrosion / irritant product : Causes skin irritation
- Serious eye damage / eye irritant product : Causes serious eye irritation
- Respiratory or skin sensitization product : Not a skin sensitizer
- Carcinogenicity product : May cause cancer
- Carcinogenic risk to humans : Overall elevation: 1 -- Carcinogenic to humans
- U.S. NTP Report on carcinogen : Reasonably anticipated to be a Human Carcinogen
- In vitro product : Suspected of causing genetic defects.
- In vivo product : Suspected of causing genetic defects.
- Reproductive toxicity product : No components toxic to reproduction
- STOT - Single Exposure product : May cause respiratory irritation. May cause drowsiness or dizziness.
- STOT - Repeated exposure product : No data available.
- Target organs : Potential hazard to the nervous system, liver, lungs, and kidneys.
- Aspiration hazard product : Not classified.
- Other effects : None known.

### SECTION 12: Ecological information

#### 12.1. Toxicity

- Ecotoxicity : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Do not empty into drains. The product contains following substances which are hazardous for the environment. Contains a substance which is: Harmful to aquatic organisms. Toxic to aquatic organisms.
- Fish product : LC 50 (Fathead minnow), 96 hr: 31.4—71.8 mg/l, Mortality  
LC 50 (Bluegill), 96 hr: 39-54 mg/l, Mortality  
EC 50 (Fathead minnow), 96 hr: 18.4—28.5 mg/l, Intoxication
- Aquatic invertebrates product : LC 50 (Water flea), 48 hr: 12—26 mg/l, Mortality
- Chronic Hazards to the Aquatic Environment**
- Fish product : No data available
- Aquatic invertebrates product : No data available
- Toxicity to aquatic plants product : No data available

#### 12.2. Persistence and degradability

##### Natco Inner Liner Repair Seal

Persistence and degradability

Persistence is unlikely based on information available.  
There is no data on the degradability of this product.



# Natco Inner Liner Repair Seal

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 06/11/2019

Revision date: 01/06/2020

Version: 2.0

### 12.3. Bioaccumulative potential

#### Natco Inner Liner Repair Seal

Bioaccumulative potential	No information available.
---------------------------	---------------------------

### 12.4. Mobility in soil

Will likely be mobile in the environment due to its volatility.

### 12.5. Other adverse effects

Other information : Harmful to aquatic life with long lasting effects.





## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste from residues / unused products : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any federal, state, provincial and regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled, Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe manner. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld, or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Waste disposal must be in accordance with appropriate Federal, State, Provincial, and local regulations.

## SECTION 14: Transport information

### 14.1. Basic shipping description

	DOT Classification	TDG	IMDG	IATA
Identification Number	UN 1710	UN 1710	UN 1710	UN 1710
Proper Shipping Name	Trichloroethylene	Trichloroethylene	Trichloroethylene	Trichloroethylene
Transport Hazard Class	6.1, Toxic Substance	6.1, Toxic Substance	6.1, Toxic Substance	6.1, Toxic Substance
Label				
Packaging Group	III	III	III, EmS #: F-A, S-A	III
Special precautions / Other information	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. The description shown may not apply to all shipping situations. Consult 40CFR, or appropriate Dangerous Goods Regulations, for additional description requirements and mode-specific or quantity-specific shipping requirements.			

# Natco Inner Liner Repair Seal

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 06/11/2019

Revision date: 01/06/2020

Version: 2.0

### SECTION 15: Regulatory information

All of the components in the product are on the following Inventory lists: X = listed International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Trichloroethylene	X	X	-	201-167-4	-		X	X	X	X	X

#### Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

#### 15.1. National regulations

#### 15.2. International regulations

##### TSCA 12(b)

Not applicable

Component	TSCA 12(b)
Trichloroethylene	Section 5

##### SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Trichloroethylene	79-01-6	100	0.1

##### SARA 311/312 Hazard Categories

Acute Health Hazard	: Yes
Chronic Health Hazard	: Yes
Fire Hazard	: No
Sudden Release of Pressure Hazard	: No
Reactive Hazard	: No

##### CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Trichloroethylene	X	100 lb	X	X

##### Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Trichloroethylene	X		-

OSHA Occupational Safety and Health Administration : Not applicable

##### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Trichloroethylene	100 lb 1 lb	-

##### California Proposition 65

This product contains the following proposition 65 chemicals

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Trichloroethylene	79-01-6	Carcinogen Developmental Male Reproductive	14 µg/day 50 µg/day	Developmental Carcinogen



# Natco Inner Liner Repair Seal

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 06/11/2019

Revision date: 01/06/2020

Version: 2.0

### U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Trichloroethylene	X	X	X	X	X

### U.S. Department of Transportation

Reportable Quantity (RQ): : Yes  
DOT Marine Pollutant : No  
DOT Severe Marine Pollutant : No

**U.S. Department of Homeland Security** : This product does not contain any DHS chemicals.

### Other International Regulations

**Mexico - Grade** : No information available

## SECTION 16: Other information

Date of issue : 06/11/2019  
Revision date : 01/06/2020  
Other information : None.  
Prepared by : Technical / Safety Department

SDS Canada (GHS)

*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*